

CORTIS SHT 200



Lubrication



Oils for moving parts operating at very high temperatures.

APPLICATIONS

Moving parts operating at very high temperatures

- **CORTIS SHT** is a synthetic oil that is particularly suitable for lubricating moving parts operating at very high temperatures.
- roller chains, conveyor rollers, and cams operating in furnaces and ovens.
- manufacture of glass containers: feeder and is machine mechanisms.
- chains and bars in continuous wood panel production machines.

ADVANTAGES

- Ensures continuous lubrication of mechanisms at temperatures up to 240°C.
- Provides excellent protection for moving metal parts operating at high temperature: anti-wear properties enhanced for high temperatures.
- No formation of hard, tough deposits, gum, or varnish at high temperature: outstanding thermal stability.
- Ensures superbly clean lubrication circuits and lubricated parts: very good detergent properties when hot.
- Very good anti-corrosion properties: protects metal parts.

TYPICAL CHARACTERISTICS	METHODS	UNITS	CORTIS SHT 200
Density at 15 °C	ISO 3675	kg/m ³	955
Viscosity at 40 °C	ISO 3104	mm ² /s	195
Viscosity at 100 °C	ISO 3104	mm ² /s	18.5
Viscosity index	ISO 2909	-	105
Pour point	ISO 8016	°C	- 33
Open cup flash point	ISO 2592	°C	265
Ash content	ISO 6245	% by weight	0.10

Above characteristics are mean values given as an information.

TOTAL LUBRIFIANTS
Industrie & Spécialités
13-10-2011 (supersedes 14-10-2004)
CORTIS SHT 200
1/1



This lubricant used as recommended and for the application for which it has been designed does not present any particular risk.
A material safety data sheet conforming to the regulations in use in the E.C. can be obtained from your local commercial adviser or down loaded from www.quick-fds.com.